

鋁隔板式高效率空氣過濾器

Separator Capacity HEPA filter

特徵 Features

效率Efficiency : PAO 99.99%、99.995% at 0.3 μ m
標準Std. : EN1822 · Class H13 / H14

使用條件Operating conditions

耐用溫度Temperature : 80°C
耐用溼度Humidity : 100%RH (NO Dew)



標準型Standard Capacity

尺寸Dimension WxDxH (mm)	風量Air Volume				初期壓損 Initial P.D (Pa)	最終壓損 Final P.D (Pa)
	H13		H14			
	CMM	CFM	CMM	CFM		
305x305x290	7	250	6	227	249 (25.4 mmH2O)	500 (50.8 mmH2O)
305x610x290	15	527	14	480		
610x610x290	31	1111	29	1012		
760x610x290	40	1399	36	1273		
915x610x290	48	1696	44	1544		
1220x610x290	65	2280	59	2076		

大風量High Capacity

尺寸Dimension WxDxH (mm)	風量Air Volume				初期壓損 Initial P.D (Pa)	最終壓損 Final P.D (Pa)
	H13		H14			
	CMM	CFM	CMM	CFM		
305x305x290	10	336	9	304	249 (25.4 mmH2O)	500 (50.8 mmH2O)
305x610x290	20	709	18	642		
610x610x290	42	1496	38	1354		
760x610x290	53	1883	48	1704		
915x610x290	65	2283	59	2066		
1220x610x290	87	3070	79	2778		

※ 特殊尺寸及規格可依客戶需求製作。 Customized size and specification are available to meet customer's requirements.

