

V-Bank高效率空氣過濾器

V-Bank Capacity HEPA filter

特徵 Features

效率Efficiency : PAO 99.99%、99.995% at 0.3 μ m
標準Std. : EN1822 · Class H13 / H14

使用條件Operating conditions

耐用溫度Temperature : 80°C
耐用溼度Humidity : 100%RH (NO Dew)



標準型Standard Capacity

尺寸Dimension WxDxH (mm)	風量Air Volume				初期壓損 Initial P.D (Pa)	最終壓損 Final P.D (Pa)
	H13		H14			
	CMM	CFM	CMM	CFM		
305x610x292	25	900	23	815	249 (25.4 mmH ₂ O)	500 (50.8 mmH ₂ O)
610x610x292	51	1800	46	1630		

大風量High Capacity

尺寸Dimension WxDxH (mm)	風量Air Volume				初期壓損 Initial P.D (Pa)	最終壓損 Final P.D (Pa)
	H13		H14			
	CMM	CFM	CMM	CFM		
305x610x292	28	1000	26	920	249 (25.4 mmH ₂ O)	500 (50.8 mmH ₂ O)
610x610x292	57	2000	52	1840		

※ 特殊尺寸及規格可依客戶需求製作。 Customized size and specification are available to meet customer's requirements.

