

紙框、金屬框折景式空氣過濾網

Pleated Air Filter

特徵 Features

Test Method 測試方法	Dot Spot Efficiency (in NBS) 比色法 比色法	Arrestance (in AFI) 比重法 比重法
	30~35%	90~94%
	ASHRAE Standard 52.1-1992(Equal to EN779)	

材質、使用條件 Material and Service Conditions

外框 Frame	紙框、鍍鋅鐵框、鋁框、不鏽鋼框 Paper Frame、Galvanized Steel、Aluminum、Stainless Steel		
濾材 Media	不織布棉和合成纖維混紡 Special Blended of Nonwoven Cotton and Synthetic Fibers		
支撐網 Support Grid	抗蝕性的金屬支撐網，採楔形結構 Anticorrosion Metal Support Grid w/Radial Wedge Pleats		
最高使用溫度 Maximum Temperature	40°C	最高使用濕度 Highest Humidity	98%RH (無結霜狀態下)

效率性能表 Performance Data

通稱尺寸 WxHxD (inch) Nominal Size	實際尺寸 WxHxD (mm) Actual Size	額定風量 (CMH) Rated Capacity	壓力損失 Pressure Drop (Pa)	
			初期壓損 Initial P.D	最終壓損 Final P.D
12x24x1	289x595x22	1700	87	130
20x20x1	492x492x22	2380		
20x24x1	492x595x22	2800		
24x24x1	595x595x22	3400		
12x24x2	289x595x45	1700	65	130
20x20x2	492x492x45	2380		
20x24x2	492x595x45	2800		
24x24x2	595x595x45	3400		
12x24x4	289x595x95	1700	50	130
24x24x4	595x595x95	3400		

※ 特殊尺寸及規格可依客戶需求製作。 Customized size and specification are available to meet customer's requirements.

