

**耐高溫鋁隔板式高效率空氣過濾器**
**Separator Capacity HEPA filter**
**特徵 Features**

 效率Efficiency : PAO 99.99%、99.995% at 0.3 $\mu$ m

標準Std. : EN1822 · Class H13 / H14

**使用條件 Operating conditions**

耐用溫度Temperature : 250°C

耐用溼度Humidity : 100%RH ( NO Dew )


**標準型 Standard Capacity**

尺寸Dimension WxDxH (mm)	風量Air Volume				初期壓損 Initial P.D (Pa)	最終壓損 Final P.D (Pa)
	H13		H14			
	CMM	CFM	CMM	CFM		
305x305x290	7	250	6	227	249 (25.4 mmH <sub>2</sub> O)	500 (50.8 mmH <sub>2</sub> O)
305x610x290	15	527	14	480		
610x610x290	31	1111	29	1012		
760x610x290	40	1399	36	1273		
915x610x290	48	1696	44	1544		
1220x610x290	65	2280	59	2076		

**大風量 High Capacity**

尺寸Dimension WxDxH (mm)	風量Air Volume				初期壓損 Initial P.D (Pa)	最終壓損 Final P.D (Pa)
	H13		H14			
	CMM	CFM	CMM	CFM		
305x305x290	10	336	9	304	249 (25.4 mmH <sub>2</sub> O)	500 (50.8 mmH <sub>2</sub> O)
305x610x290	20	709	18	642		
610x610x290	42	1496	38	1354		
760x610x290	53	1883	48	1704		
915x610x290	65	2283	59	2066		
1220x610x290	87	3070	79	2778		

※ 特殊尺寸及規格可依客戶需求製作。 Customized size and specification are available to meet customer's requirements.

